


DOUBLE PARKING SPACE HEAD-ON PARKING WITH VAN ACCESSIBLE AISLE FOR HANDICAP ACCESS


CHART A

Required Accessible Spaces in Parking Areas*

Total Parking Spaces in Parking Area	Required Minimum Number of Accessible Spaces		
1 to 25	1		
26 to 50	2		
51 to 75	3		
76 to 100	4		
101 to 150	5		
151 to 200	6		
201 to 300	7		
301 to 400	8		
401 to 500	9		
501 to 1,000	2 percent of total		
over 1,000	20 plus 1 for each 100		
based on "Americans with Disibilities Act" Design			

* Chart based on "Americans with Disibilities Act" Design Guide.





HEAD-ON PARKING

CHART B

Parking Layout Dimensions for 9-ft. wide stalls*

Angle A	45 ⁰	60 ⁰	75 ⁰	90 ⁰
Minimum Length of stall B	25'	22'	20'	18.5'
Stall width, C, parallel to aisle	12.7'	10.4'	9.3'	9.0'

* Chart based on dimensions recommended in "Parking Principles".

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL HIGHWAY ADMINISTRATION EASTERN FEDERAL LANDS HIGHWAY DIVISION

U.S. CUSTOMARY DETAIL

PAVEMENT MARKINGS IN PARKING AREAS

NO SCALE

DETAIL APPROVED FOR USE	DETAIL
EVISED: 03/07	E634-05